

Brakes · Wheels · Tires

B

Date introduced	Chassis No.	Unit No.	Modification
22 Sept. 61	O 001 579		<u>Brake shoes</u> Now: Lighter web Formerly: Continuous web
13 Oct. 61	842 877		<u>Hand brake lever</u> Now: Hand brake lever pin with deeper groove for new spring clip Formerly: Circlip

Date introduced	Chassis No.	Unit No.	Modification
<u>1962</u>			
11 Jan. 62	0 009 330 (361)	-	Brake master cylinder 20.64 dia.
8 Mar. 62	0 024 846	-	Now: Stroke 36 mm Formerly: 30 mm (temporary measure 33 mm)
1 Feb. 62	0 016 896	-	Wheel disc Now: Metal thickness 3 + 0.25 mm Formerly: 2.75 + 0.25 mm Now: Inside rim raised to 11 mm Formerly: 8 mm
21 Mar. 62	0 027 850	0 028 672	Wheel brake cylinder, front Now: 22.2 mm dia. Formerly: 20.64 mm dia.
5 Apr. 62	4 630 938 (111/112) (115/116)	-	Brake System Now: Hydraulic Formerly: Mechanical
13 Apr. 62	0 036 000	-	Brake nose, front Now: 300 mm long Brake nose holder repositioned -3 mm forward Formerly: 415 mm long
28 Apr. 62	938 139	-	Brake fluid reservoir Now: Plastic type (transparent) Formerly: Aluminium
9 May 62	0 042 95-	0 044 065	Front wheel cylinder connecting pipe Now: 185 mm long Formerly: 230 mm
14 Aug. 62	980 721	HA 5 066 801 VA 938 448	Brake lining Now: Jurid 120 Formerly: Jurid 826 and K3
21 Aug. 62	0 076 300	-	Brake shoe, rear Now: 5 mm wide, effective brake lining surface 130 sq. cm. Formerly: 40 mm wide, brake lining surface 830 sq. cm.

Date introduced	Chassis No.	Unit-No.	Modification
10 Sept. 62	0 086 122	-	<u>Reservoir for brake fluid</u>
18 Sept. 62	4 978 442	-	Now: Screw top Formerly: Stopper
14 Sept. 62	0 086 985 (M 267)	-	<u>Tires</u> Now: 6.00 - 15.6 PR Formerly: 6.00 - 15
<u>1963</u>			
7 Jan. 63	1 041 014(M 216)	-	<u>Brakes</u> Now: Main brake cylinder 36 mm stroke Now: Brake drum 250 mm dia Now: Brake shoes, front 55 mm wide, rear 45 mm wide Now: Straight brake shoe ends

Date introduced	Chassis No.	Unit No.	Modification
5 Aug. 63	5 677 119(113/114) (117/118) 1 144 303(221-223) (241-251) 0 221 975	-	Hub cap for disc wheel Now: VW sign no longer in colour
5 Aug. 63	0 221 975(311-314) (361-364)	-	Wheel Now: With rim embellishers
5 Aug. 63	0 215 175(343/345)	-	Tires Now: Reinforced designation 600 S 15 L
5 Aug. 63	5 677 119	-	Tires 5.60-15 Now: Pressure, rear 1.7 atü (24 psi) Formerly: 1.6 atü (23 psi)
5 Aug. 63 19 Dec. 63	1 145 427(2/1t) 1 222 026(2/2t) 4	-	Tires Now: Size 700 - 14 (tubeless) Formerly: 6.40-15 (with tube)
16 Oct. 63	0 269 000	-	Disc wheel Now: Without slots Now: Pressed-in lugs to secure the wheel cap
1964			
21 Jan. 64	0 335 480	YA 0 340 764	Brake drum, front Now: Inner diameter of the wheel hub 32 mm Formerly: 34 mm
April 64	0 397 311	-	Front wheel brake 248 mm dia. Now: Return spring tension increased.
1 Apr. 64	6 240 561	HA 6 744 039	Brake lining, rear Now: Jurid 120 Formerly: Jurid K 3
4 May 64	0 427 460	VA 0 427 494	Brake lining, front Now: Energit 334 Formerly: Jurid 825

Date introduced	Chassis No.	Unit No.	Modification
20 May 64	0 437 585	HA 0 436 735	<u>Brake lining, rear</u> Now: Energit 334 Formerly: Jurid 825
15 June 64	0 469 483	-	<u>Cap of brake fluid reservoir</u>
22 June 64	0 458 860	-	Now: With three ventilation holes Formerly: One ventilation hole
7 July 64	0 481 065	-	<u>Master cylinder</u> Now: Washer for master cylinder plug with oval hole.
3 Aug. 64	315 000 001	0 485 456	<u>Brake shoes</u> Now: End faces of the brake shoe web remachined to 90° + 1° 30'
3 Aug. 64	115 000 001	-	<u>Brake hose, front</u> Now: Type 2 brake hoses now installed
3 Aug. 64	315 000 001	-	<u>Tires</u> Now: Tire pressures altered.
3 Aug. 64	315 000 001	-	<u>Brake lines - Master cylinder - Brake fluid reservoir</u> Now: Larger cross section Outside diameter/wall thickness 6.00 x 0.7 mm Formerly: 4.75 x 0.72 mm <u>Fluid reservoir for master cylinder</u> Now: Brake line connected to reservoir with union nut Now: Cap with three ventilation holes and rubber sealing ring. <u>Master Cylinder</u> Now: For Variant 20.64 mm dia. Now: Master cylinder plug for 6 mm fluid line square on upper shoulder.

Date introduced	Chassis No.	Unit No.	Modification
3 Aug. 64	115 000 001	-	<p><u>Master cylinder</u> Now: 17.62 mm dia. - stroke 33 mm Formerly: 19.05 mm dia. - stroke 30 mm Now: Pressure end of operating rod relieved behind head Now: The angle of stop on the foot brake pedal 30° Formerly: 7°</p> <p><u>Brake hose, front</u> Now: Brake hose bracket inclined outwards and spot welded onto lower part of frame head. Hose installed without twist and hanging downwards</p> <p><u>Brake back plate and brake shoes</u> Now: Additional contact surface on brake back plate (Three point contact) Now: Slots in wheel cylinder piston made wider Now: Ends of shoes angled. Brake shoe mounting box shaped</p> <p><u>Brake drum, rear</u> Now: Drilling for securing oil deflector discontinued</p>
4 Aug. 64	265 004 735	7 172 236	<u>Brake wheel cylinder, rear</u> Now: Piston lengthened 2 mm
26 Aug. 64	315 022 105 (311-314) (343-346) (361-364)	-	<u>Wheel trim ring</u> Now: Outer diameter reduced
10 Sept. 64	115 116 205	7 153 665	<u>Brake lining, rear</u> Now: Energit 335 Formerly: Energit 717
11 Sept. 64	255 026 862	-	<u>Brake pedal</u> Now: Tube for pedal lengthened. Washer for return spring discontinued.
20 Nov. 64	115 306 919	6 770 070	<u>Brake shoe retaining pin, front</u> Now: 40 mm long Formerly: 35 mm
15 Dec. 64	315 091 887	0 576 701	<u>Brake drum, rear</u> Now: Material GTS 55 Formerly: GTS 45

Date introduced	Chassis No.	Unit No.	Modification
1965			
4 Jan. 65	115 358 743	-	<u>Master Cylinder operating rod</u>
15 Jan. 65	315 103 591		Now: 9 mm dia. Formerly: 8 mm dia.
6 Jan. 65	315 099 066	0 587 660	<u>Front brake drums</u> Now: Material GTS 55 Formerly: GTS 45
1 Feb. 65	115 400 026	7 675 524	<u>Retaining pin rear brakes</u> Now: 32 mm long Formerly: 28 mm
1 Feb. 65	115 400 109	-	<u>Hand brake</u>
	235 098 337(M 36)	-	Now: With hand brake cable
19 Mar. 65	365 144 906	-	equalizer, hand brake cable lengthened.
3 Feb. 65	315 115 593	0 605 585	<u>Brake lining, front-Pagid</u> Now: Quality altered (dark grey colour).
4 Feb. 65	315 115 000	-	<u>Disc wheel with tubeless tire</u> Now: Dyanamically balanced.
24 May 65	115 844 631	8 065 145	<u>Brake lining, rear</u> Now: Jurid 334 P. Formerly: Jurid 335.
9 June 65	115 912 780	7 354 433	<u>Brake lining, front</u> Now: Jurid 334 P. Formerly: Jurid 335.

Date introduced	Chassis No.	Unit No.	Modification
2 Aug. 65	316 000 001	-	<p><u>Front wheels</u> Now: Disc brakes Formerly: Drum brakes</p>
2 Aug. 65	116 000 001	-	<p><u>Brake drums</u> Now: Hubs with stiffening ribs; on the rear brake drums the measurement from wheel disc contact surface to drum hub contact surface has been increased Now: Track width at rear 1300 mm Formerly: 1288 mm</p>
2 Aug. 65	116 000 001 316 000 001	-	<p><u>Tires</u> Now: New tires pressures laid down</p>
2 Aug. 65	116 000 001 316 000 001	-	<p><u>Wheel discs</u> Now: Slotted wheel discs</p> <p><u>Wheel bolts - Type 3</u> Now: 4 - M 14 x 1.5 tightening torque 94 ft.lbs (13 mkg); pitch circle diameter 130 mm Formerly: 5 - M 12 x 1.5; tightening torque 72 ft.lbs. (10 mkg); pitch circle 205 mm dia.</p> <p><u>Wheel caps</u> Now: Modified shape</p> <p><u>Wheel embellisher</u> Now: To suit the modified wheel disc.</p>
21 Sept. 65	216 031 588	1495 481	<p><u>Brake drum, front</u> Now: Hardness 180-220 BE, identity mark "5" Formerly: Hardness 160-200 BE</p>
24 Nov. 65	316 104 898	-	<p><u>Brake hose, front</u> Now: 355 mm long Formerly: 380 mm</p>
3 Dec. 65	316 115 000	-	<p><u>Wheel caps for disc wheels</u> Now: Holes for cap removal tool repositioned towards outside.</p>

Date introduced	Chassis	Unit No.	Modification
1966			
3 Jan. 66	116 419 964	7 919 960	<u>Brake lining, front</u> Now: Textar TE-18 Formerly: Textar V-643
1 Mar. 66	316 199 873		<u>Brake shoes, rear</u> Now: With bonded lining Formerly: Riveted Now: Brake shoe flange 3.5 mm Formerly: 3 mm
6 Apr. 66	346 225 726		<u>Brake line brake master cylinder - fluid reservoir</u> Now: Shape and length modified reservoir positioned higher
12 May 66	116 872 032		<u>Fluid reservoir</u> Now: With sediment trap and screw cap. Brake line to the master cylinder modified.
1 Aug. 66	117 000 003 (1/1500)	-	<u>Front wheels</u> Now: Disc brakes Formerly: Drum brakes
1 Aug. 66	147 000 004 157 000 005 347 000 005		<u>Brake system</u> Now: Dual circuit system
14 Dec. 66	217 072 466 317 000 001) 367 000 004)		only for certain
1 Sept. 66	117 000 001) 217 019 924)		export countries

Date introduced	Chassis No.	Unit No.	Modification
1 Aug. 66	117 000 001 (1/1200)	} only for certain export countries	<u>Drum brakes</u> Now: Brake hose bracket on lower part of frame head repositioned, brake hose altered.
	117 000 002 (1/1300)		
	117 000 003 (1/1500)		
	157 000 005		
			<u>Brake back plates, rear</u> Now: With two adjusting holes and two inspection holes
			<u>Increased width of track</u> Now: Hand brake cable longer brake lines modified.
1 Aug. 66	317 000 001		<u>Brake line between fluid reservoir and master cylinder</u> Now: Thickness of galvanized coating 25 Formerly: 12
1 Aug. 66	317 000 001		<u>Brake line between fluid reservoir and master cylinder</u> Now: Cross section increased outer dia./wall thickness 6.00 x 0.7 mm Formerly: 4.75 x 0.72 mm Now: Fluid reservoir and sealing plug for brake line modified
1 Aug. 66	117 000 003 (1/1500)	-	<u>Disc wheels for disk brakes</u> Now: 4 wheel bolts M 14x1.5, tightening torque 13 mkg. Hole pitch circle 130 mm. Formerly: 5 - M12x1.5, tightening torque 10 mkg, hole pitch circle 250 mm.

Date introduced	Chassis No.	Unit No.	Modification
			<u>Wheel caps</u> Now: Shape modified
			<u>Tim rings</u> Now: Made to fit the modified wheel discs
15 Sept.66	117 180 343 (11)	-	<u>Stop plate for brake and clutch pedals</u> Now: Stop increased in height to 11 mm Formerly: 10 mm
16 Sept.66	147 157 415 (14, 15)	-	
16 Sept.66	317 047 326	-	<u>Hole in rear cross member for brake line</u> Now: Sealing sleeve modified
3 Oct. 66	147 245 980 (141-144)	-	<u>Tires</u> Now: Marked 5.60 S 15 4 PR Formerly: 5.60-15 4 PR
17 Nov. 66	117 349 409 (11/1500)	-	<u>Brake fluid reservoir for single circuit brake system</u> Now: Positioned 17 mm higher
27 Dec. 66	117 398 501	-	<u>Wheel caps</u> Now: Shape modified
6 Jan. 67	317 139 333	-	

Date introduced	Chassis No.	Unit No.	Modification
<u>1967</u>			
5 Jan. 67	117 469 710	(single circuit brakes)	Feed line from reservoir to the master cylinder
18 Jan. 67	117 488 486	(single circuit brakes)	
6 April 67	317 175 741	(dual circuit brakes)	Now: Cross section 8.00 x 0.7mm
7 April 67	117 626 506	(dual circuit brakes)	Formerly: 6.00 x 0.7 mm
17 April 67	147 657 893	(dual circuit brakes)	
	157 658 059	(dual circuit brakes)	
19 April 67	347 173 855	(dual circuit brakes)	
26 April 67	317 186 575	-	Wheel disc
10 Oct. 67	118 227 175	-	Now: Hump type rim
26 May 67	217 131 259	-	Brake line between T piece and brake hose, rear, right Now: Distance to the transmission maintained by a bracket